




DIN SPROCKET



12B-1-2




NOTE	mm
Pitch	19.05
Roller Φ	12.07
h	11.1
h1	10.8
h2	30.3

Dimensions: mm

Teeth	OD	Bore:d	Type B Simplex		Type B Duplex			Material
			Hub		Hub		Bore:d	
			BD	BL	BD	BL		
8	57.6	12	31	30	31	45	12	C45
9	62.0	12	37	30	37	45	12	
10	69.0	12	42	30	42	45	12	
11	75.0	14	46	35	47	50	16	
12	81.5	14	52	35	53	50	16	
13	87.5	14	58	35	59	50	16	
14	93.6	14	64	35	65	50	16	
15	99.8	14	70	35	71	50	16	
16	105.5	16	75	35	77	50	20	
17	111.5	16	80	35	83	50	20	
18	118.0	16	80	35	89	50	20	
19	124.2	16	80	35	95	50	20	
20	129.7	16	80	35	100	50	20	
21	136.0	20	90	40	100	50	20	
22	141.8	20	90	40	100	50	20	
23	149.0	20	90	40	110	50	20	
24	153.9	20	90	40	110	50	20	
25	160.0	20	90	40	120	50	20	
26	165.9	20	95	40	120	50	20	
27	172.3	20	95	40	120	50	20	
28	178.0	20	95	40	120	50	20	
29	184.1	20	95	40	120	50	20	
30	190.5	20	95	40	120	50	20	
31	196.3	20	100	40	130	50	20	
32	203.3	20	100	40	130	50	20	
33	209.3	20	100	40	130	50	20	
34	214.6	20	100	40	130	50	20	
35	221.0	20	100	40	130	50	20	
36	226.8	20	100	40	130	50	25	
37	232.9	20	100	40	130	50	25	
38	239.0	20	100	40	130	50	25	
39	245.1	20	100	40	130	50	25	
40	251.3	20	100	40	130	62	25	
42	264.5	25	118	61	136	62	25	
45	282.5	25	118	61	136	62	25	
46	287.9	25	118	61	136	62	25	
48	300.1	25	118	61	136	62	25	
50	312.3	25	118	61	136	62	25	
55	342.7	25	118	61	136	62	25	
57	355.4	25	118	61	136	62	25	
60	373.0	25	118	61	136	62	25	
76	469.9	30	118	61	145	63	30	
95	585.1	30	133	62	145	63	30	

* Plate wheel

DIN SPROCKET



16B-1-2




NOTE	mm
Pitch	25.4
Roller Φ	15.88
h	16.2
h1	15.8
h2	47.7

Dimensions: mm

Teeth	OD	Bore:d	Type B Simplex		Type B Duplex			Material
			Hub		Hub		Bore:d	
			BD	BL	BD	BL		
8	77.0	16	42	35	42	65	16	C45
9	85.0	16	50	35	50	65	16	
10	93.0	16	55	35	56	65	16	
11	99.5	16	61	40	64	70	20	
12	109.0	16	69	40	72	70	20	
13	117.0	16	78	40	80	70	20	
14	125.0	16	84	40	88	70	20	
15	133.0	16	92	40	96	70	20	
16	141.0	20	100	45	104	70	20	
17	149.0	20	100	45	112	70	20	
18	157.0	20	100	45	120	70	20	
19	165.2	20	100	45	128	70	20	
20	173.2	20	100	45	130	70	20	
21	181.2	20	110	50	130	70	25	
22	189.3	20	110	50	130	70	25	
23	197.5	20	110	50	130	70	25	
24	205.5	20	110	50	130	70	25	
25	213.5	20	110	50	130	70	25	
26	221.6	20	120	50	130	70	25	
27	229.6	20	120	50	130	70	25	
28	237.7	20	120	50	130	70	25	
29	245.8	20	120	50	130	70	25	
30	254.0	20	120	50	130	70	25	
31	262.0	25	120	50	140	70	25	
32	270.0	25	120	50	140	70	25	
33	278.5	25	120	50	140	70	25	
34	287.0	25	120	50	140	70	25	
35	296.2	25	120	50	140	70	25	
36	304.6	25	120	50	140	70	25	
37	312.6	25	120	50	140	70	25	
38	320.7	25	120	50	140	70	25	
39	328.8	25	120	50	140	70	25	
40	336.9	25	120	50	140	70	25	
42	353.0	25	133	68	140	70	25	
45	377.1	25	133	68	140	70	25	
46	385.2	25	133	68	140	70	25	
48	401.3	25	133	68	140	70	25	
50	417.4	25	133	68	140	70	25	
57	474.0	30	133	68	160	82	40	
60	498.3	30	133	68	160	82	40	
76	627.0	30	145	68	160	82	40	
95	781.1	30	160	78	180	109	40	

* Plate wheel

DIN SPROCKET



20B-1-2

NOTE	mm
Pitch	31.75
Roller Φ	19.05
h	18.5
h1	18.2
h2	54.6

Dimensions: mm

Teeth	OD	Bore:d	Type B Simplex		Type B Duplex			Material
			Hub		Hub		Bore:d	
			BD	BL	BD	BL		
8	98.1	20	53	40	53	75	20	C45
9	108.0	20	63	40	63	75	20	
10	117.9	20	70	40	70	75	20	
11	127.8	20	77	45	80	80	20	
12	137.8	20	88	45	90	80	20	
13	147.8	20	98	45	100	80	20	
14	157.8	20	108	45	110	80	20	
15	167.9	20	118	45	120	80	20	
16	177.9	25	120	50	120	80	25	
17	187.9	25	120	50	120	80	25	
18	198.0	25	120	50	120	80	25	
19	208.1	25	120	50	120	80	25	
20	218.1	25	120	50	120	80	25	
21	228.2	25	140	55	140	80	25	
22	238.3	25	140	55	140	80	25	
23	248.3	25	140	55	140	80	25	
24	258.4	25	140	55	140	80	25	
25	268.5	25	140	55	140	80	25	
26	278.6	25	150	55	150	80	25	
27	288.6	25	150	55	150	80	25	
28	298.7	25	150	55	150	80	25	
29	308.8	25	150	55	150	80	25	
30	318.9	25	150	55	150	80	25	
31	329.0	25	150	55	150	80	25	
32	339.1	25	150	55	150	80	25	
33	349.2	25	150	55	150	80	25	
34	359.3	25	150	55	150	80	25	
35	369.4	25	150	55	150	80	25	
36	379.5	25	150	55	150	80	30	
37	389.5	25	150	55	150	80	30	
38	399.6	25	150	55	150	80	30	
39	409.7	25	150	55	150	80	30	
40	419.8	25	150	55	150	80	30	
42	440.0	30	160	80	160	101	30	
45	470.3	30	160	80	160	101	30	
46	480.4	25	160	80	160	101	30	
48	500.6	25	160	80	160	101	30	
50	520.8	25	160	80	160	101	30	
57	591.5	30	160	80	180	116	40	
60	621.8	30	160	80	180	116	40	
76	783.5	30	160	80	180	116	40	
95	975.2	30	168	93	200	116	40	

* Plate wheel